

sales@globomotive.com



ABOUT GLOBOMOTIVE GROUP

Globomotive Group over the past decade has been involved in Research and Development, Supplying, Manufacturing of Automotive Consumables, Industrial and Electrical Consumables, Fasteners and Fittings and Fabrication of various Ferrous/Non Ferrous Metal Products. "Delivering Business" being the main motto of our Company, we develop technology and products as per our Customers requirement to differentiate our self as a Customer Focused Company.

We currently have local presence in 3 Continents with offices in U.S., U.K. and India. However, most of our manufacturing and developing interest lies in South-East Asia, primarily in India, China, Malaysia and Taiwan.

Globomotive differentiates itself process oriented organization rather than product oriented which has helped to develop our footprints across the globe. Our processes include but are not restricted to Extrusion, Annealing, Forging, Electron Beaming, and Stamping etc. which has empowered us to provide high quality and innovative products.

Globomotive is an ISO 9001 certified company and proud member of FIEO (Federation of Indian Export Organizations). Our Products conforms and are approved by high global quality standards, to name few, UL (Underwriters Laboratories), CE (European Conformity), IS (Indian Standard), BASEC, VDE, UKAS, PSB, SASO, RoHS, IEC standards.





















GL#B#M#IIVE GR#UP

Your Global Partners for Success



Aluminum Foil Tape

HVAC industry for joining and sealing Foil-Scrim-Kraft Facing laminated fiberglass blanket 1 duct board joints and seams: joining and sealing flexible air duct seams and connections. May also be used for other industrial uses requiring a tape with these characteristics and benefits.



Aluminum-Glass Cloth Tape

HVAC industry for joining and sealing Alum.

• Glass Facing laminated fiberglass blanket / duct board joints and seams: joining and sealing industrial pipe insulation' seams and connections. May also be used for other industrial uses requiring a tape with these characteristics and benefits.



Foil-Scrim-Kraft Tape

HVAC industry for joining and sealing Foil-Scrim
• Kraft Facing laminated fiberglass blanket duct
board joints and seams: joining and sealing
flexible air duct seams and connections. May
also be used for other industrial uses requiring a
tape with these characteristics and benefits.



PSK Facing For Metal Building TAPE

Thicker black PK Facing for Metal Building. suitable for cinema. music hall. restaurant and museum.

Utility grade PSK Facing for Metal Building Insulation. suitable for warehouse. factory, supermarket, gym, and office etc.
Utility grade black PSK Facing for Metal Building, suitable for cinema, music hall. restaurant and museum.





Cloth Duct Tape

Linen and waterproof superband which thanks to its adhesiveness, impermeability and heat resistance

- · Water and air leaks.
- Mending tears in sheets
- Mending and jointing sheets of polyethylene.
- High tensile strength.
- · Easy to tear by hand.



Masking Tape

Masking tape for car paint and general purpose Engineered with fine structure crepe backing combined with a high temperature rubber adhesive system. exhibits a smooth, consistent unwind during application. ideally suited for demanding masking applications in transportation, marine and metal fabrication industries



Double Sided Cloth Tape

Double sided cloth tape with hot melt adhesive: used for carpeting. We have different colors of release liners available, light yellow. Havana. white color. Below is the technical data:

Backing: Cloth

Adhesive: Hot melt based

Liner: light yellow. havana. white color Thickness (adhesives+cloth): 200micron

Tack rolling ball: 26#

180Peel Adhesion to steel: > 8N/25mm

Tensile Strength: 95N/25mm

Elongation: 14%

www.globomotive.com

sales@globomotive.com

INDIA Office: +91 886 600 1604 | U.S.A Office: +1 678 561 5760 U.K Office: +44772 341 4162 | China Office: +8613775114290



GL#B#M#IIVE GR#UP

Your Global Partners for Success



PVC Electrial Insulation

PVC insulating tape

The reliable and protective adhesive tape for insulating, wrapping and binding electrical wires and cables.

- · For insulating and binding electric cables
- · Protect cable coverings
- Flame-resistant & low harmful chemical substance.
- · Easy to wrap and mould around uneven surfaces
- Used under 600V and 80"C With standard EN 60454-3-1

Specifications of PVC Electrial Insulation

Code	Description	Packing	Thickness	mm	m	Peeling strength	Unit
10001	Insulating tape	10PCS cellophane	0.13	15	10	1.8N/10MM	500
10002	Insulating tape	10PCS cellophane	0.13	19	10	1.8N/10MM	500
10003	Insulating tape	10PCS cellophane	0.15	19	20	1.8N/10MM	250
10004	Wire harness tape	10PCS cellophane	0.19	19	27	1.8N/10MM	200
10005	Insulating tape	6PCS blister card	0.13	19	3	1.8N/10MM	100
10006	Insulating tape	6PCS blister card	0.13	19	3	1.8N/10MM	100
10007	Insulating tape	3PCS blister card	0.13	19	10	1.8N/10MM	100



Bopp Packing Tape

- · Packing for cartons.
- With resistant and tensile strength.
- Light / high adhesion.
- Printability.
- Suitable for auto-packing machine.



Warning Marking Tape

- Nw010
 - Power adhesive with high quality natural rubber glue coated on printed PVC film.
- Marking on the floor.
- Divide different region.
- Warning for danger.
- Easy to recognise.
- · Printed word available.











Stationery Tape

- Used to school and office, also used for gift wrapping
- Our color tape series are available in red, yellow, green, blue, purple, wite and black colors...etc. Special requests for different colors according to client's preferences are available.





Sticker

Instructions: Boat Numbers, Letters & Symbols... Before applying, clean surface of dirt. grease. wax or moisture. Press firmly to make positive contact.

Many Uses and Applications:

Use Numbers. Letters & Symbols to mark personal items or for property identification. You can use to mark vehicles such as boats, bikes, cars and trucks or use on address plates. mailboxes and more!Create fun school projects too! The possibilities are endless!

- www.globomotive.com
- sales@globomotive.com

INDIA Office: +91 886 600 1604 U.S.A Office: +1 678 561 5760 U.K Office: +44772 341 4162 | China Office: +8613775114290



GL#B#M#TIVE GR#UP

Your Global Partners for Success





Foam Tape

- · Sticky on both sides of tape.
- · Wall-mount pictures, decorations.
- Use on most types of walls. .ceramic tile. and wood- surfaces that are clean, dry and smooth.



Foam Weather Stripping

Characteristics:

- High density
- Highly elastic
- · Easy to cut



- Non-aging
- Self-adhesive
- Waterproof, anti-dust and soundproof



Pu Foam Tape

HVAC industry for joining and sealing: air conditioner, refrigerator...









PVC Foam Tape

is a medium density closed-cell polyvinyl Chloride foam. The tape provides an excellent combination of flexibility and conformability with strength and wear resistance. Performs in those-tough duty applications where tape must still flex to fit and seal. Characteristics common to all closed-cell vinyl foam products include the ability to make a long life seal against air, moisture. light and dust penetration. Closed-cell vinyl foam completely seals out air. moisture. light and dust when compressed 30% or more



PVC PE Weather Stripping

Kit Contains Enough Weatherstrip for One 3* Door.

V-Seal weatherstripping can create tighter seals around windows and doors. To tell if you need weatherstripping.atand in front of a door of window If you can Feel a draft edge of a closed door or window.you need weatherstripping

To apply to an exterior door.

- · Remove any existing weatherstripping.
- Clean surface and allow it to dry completely.
- Cut weatherstripping to destred length with scissors.
- Cresse into V-shape with adhesive side out and peet adhesive backing.
- Press in place with fingertips.
- · Apply this to door frame with creased side lacing door on all sides
- Make sure the wing is compressed by closed door.
 (Avoid touching adhesive with hands or any other surfaces).




sales@globomotive.com

INDIA Office: +91 886 600 1604 | U.S.A Office: +1 678 561 5760

U.K Office: +44772 341 4162 | China Office: +8613775114290





Metal Reinforced Corner Tape

Flexible metal corner tape is ideal for different corners and angles. It is made of paper Joint tape bonded to two corrosion resistant metal strips which has high tensile strength and rustiness resistant.

Materials: paper tape with metal reinforced. metal has Aluminum strip or zinc strip. This flexible corner tape is easy to apply like all drywall products and has so many benefits. You can cut to length to reduce waste and cost. It can be used on old and new drywall and plaster as well as all inside and outside corners.

For example: Archways. curves. vaulted ceilings. coffered ceilings, bay windows. etc. SIZE: 50mm x 30m/roll, 7.6m, or any sizes produced as per client's requirements.



Paper Drywall Joint Tape

Is suitable to be reinforced gypsum board joints and corners prior to painting. wallpapering. Type: Laser holes or pinholes on the paper for ventilation



Self-Adhesive Fiberglass Tape, Drywall Joint Tape

Is woven from fiberglass bulk yarn, then coated with alkaline resistant glue and adhesive glue. then cut into different size. This tape is very strong self-adhesive and used in various construction applications. These include reinforcing wall cracks, board cracks, plasterboard cracks and marble cement: in addition to repairing drywall joints.



Self Fusing High Voltage Rubber Tape

Self fusing rubber tape With excellent high quality rubber, apply very good insulation protective for high voltage (>=20kv) wire & cable.

- Forms a homogeneous rubber tube after application, without heat or pressure.
- Water proof, can used on cable under water.
- For permanent and temporary repairs.
- High elongation(>=1000%).
- With standard ANSI/UL 510-1994.



Anti-Slip Tape

With PVC base anti-sheet.coated with high quality acrylic glue.cut strip lengths for custom sizing.

- meets OSHA atandards and helps prevent slip-related injuries.
- durable grit surface provides long-lasting protection even when exposed to heavy traffic.
 water or grease.
- use indoors or outdoors.
- self-adhesive backing sticks to painted wood, metal and sealed concrete.
- · easy to tear by hand.



KRAFT PACKING TAPE

It is suitable for all kinds of packaging purpose like carton sealing .binding and packaging Tan color can match the carton color harmonizing the visual effects.

- www.globomotive.com
- sales@globomotive.com

INDIA Office: +91 886 600 1604 | U.S.A Office: +1 678 561 5760

U.K Office: +44772 341 4162 | China Office: +8613775114290





Anti-Scratch Felts

Anti-scratch felts can be used protect delicate surfaces or facilitate the movement of objects over smooth surfaces available in different sizes.

- · protects wood, glass and parquellaminate and tiles
- · pre-cut in different sizes or easily cut to size
- · available in while and brown



Cleaning Roller

Power adhesive masking tape with easy use roller, apply easy cleaning for cloth and leather face.

- · Residue-free removal.
- Easy to tear.
- One PC take off design, with cut liner
- Refillable



Cleaning Roller

Of GANA is an ideal material for sealing. which is widely applied in construction machinery. chemical industry and other areas. especially in pipe linking systems.

With excellent characteristics of our products such as sealing insulativity, acid-resistance. and corrosion-resistance. it can be widely used under all conditions for a tong term. Specifications of ptfe tape(teflon tape):

- Density: 0.15 2.0g/cm³
- Width: 3 100mm
- Length: 5 50m
- Thickness: 0.075 0.2mm
- Color. White or colorful
- Heat-resistance: +260°C
- Cold-resistance: -190°C
- High pressure resistance: 150 200kg/cm
- Tensile strength: 9Mpa or according to the demand
- Percentage elongation: 30%
- Completive prices
- OEM orders are welcome

Ptfe tape (teflon tape) inner packing:

10pcs wrapped in transparent shrink foil or small box



- www.globomotive.com
- sales@globomotive.com

INDIA Office: +91 886 600 1604 | U.S.A Office: +1 678 561 5760 U.K Office: +44772 341 4162 | China Office: +8613775114290

