



M22759 Mil-Spec Airframe Wire
MIL-W-22759/13 | SAE AS22759/13 & MIL-
W-22759/14 | SAE AS22759/14



MIL-W-22759/13 | SAE AS22759/13 MIL-W-22759/14 | SAE AS22759/14

CONSTRUCTION

- Tin Coated Copper
- Extruded FEP
- Clear PVDF Jacket

CHARACTERISTICS

- Temperature Range : 135°C
- Voltage Rating : 600 Volts

CONSTRUCTION

- Tin Coated Copper
- Extruded FEP
- Clear PVDF Jacket

CHARACTERISTICS

- Temperature Range : 135°C
- Voltage Rating : 600 Volts

Specifications of MIL-W-22759/13 | SAE AS22759/13 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
24	19/36	0.047	0.051
22	19/34	0.048	0.054
20	19/32	0.058	0.064
18	19/30	0.068	0.074
16	19/29	0.073	0.081
14	19/27	0.087	0.095
12	37/28	0.107	0.115
10	37/26	0.134	0.142

Specifications of MIL-W-22759/14 | SAE AS22759/14 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.035	0.039
24	19/36	0.040	0.044
22	19/34	0.045	0.051
20	19/32	0.053	0.059
18	19/30	0.063	0.069
16	19/29	0.067	0.075
14	19/27	0.083	0.091
12	37/28	0.103	0.111