



## M22759 Mil-Spec Airframe Wire MIL-W-22759/19 | SAE AS22759/19 & MIL-W-22759/20 | SAE AS22759/20



### MIL-W-22759/19 | SAE AS22759/19 MIL-W-22759/20 | SAE AS22759/20

#### CONSTRUCTION

- Silver Plated Copper
- Extruded ETFE

#### CHARACTERISTICS

- Temperature Range : -55°C to +150°C
- Voltage Rating : 600 Volts

#### APPLICATIONS

- M22759/19 wire may be used in aerospace applications where mechanical toughness and light weight are required.

#### CONSTRUCTION

- Silver Plated Copper
- Extruded ETFE

#### CHARACTERISTICS

- Temperature Range : -55°C to +150°C
- Voltage Rating : 600 Volts

#### APPLICATIONS

- M22759/20 wire may be used in aerospace applications where mechanical toughness and light weight are required.

### Specifications of MIL-W-22759/19 | SAE AS22759/19 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.030	0.034
24	19/36	0.034	0.038
22	19/34	0.041	0.045
20	19/32	0.049	0.053

### Specifications of MIL-W-22759/20 | SAE AS22759/20 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.030	0.034
24	19/36	0.034	0.038
22	19/34	0.041	0.045
20	19/32	0.049	0.053