



M22759 Mil-Spec Airframe Wire MIL-W-22759/81 | SAE AS22759/81 & MIL-W-22759/82 | SAE AS22759/82



MIL-W-22759/81 | SAE AS22759/81 MIL-W-22759/82 | SAE AS22759/82

CONSTRUCTION

- Silver coated high strength copper alloy
- Fluoropolymer/polyimide tapes Insulation

CHARACTERISTICS

- Temperature Range : 200°C
- Voltage Rating : 600 Volts

CONSTRUCTION

- Nickel coated high strength copper alloy
- Fluoropolymer/polyimide tapes Insulation

CHARACTERISTICS

- Temperature Range : 260°C
- Voltage Rating : 600 Volts

Specifications of MIL-W-22759/81 | SAE AS22759/81 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.030	0.034
24	19/36	0.034	0.038
22	19/34	0.040	0.043
20	19/32	0.048	0.051

Specifications of MIL-W-22759/82 | SAE AS22759/82 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.030	0.034
24	19/36	0.034	0.038
22	19/34	0.040	0.043
20	19/32	0.048	0.051