



M22759 Mil-Spec Airframe Wire MIL-W-22759/89 | SAE AS22759/89 & MIL-W-22759/90 | SAE AS22759/90



MIL-W-22759/89 | SAE AS22759/89 MIL-W-22759/90 | SAE AS22759/90

CONSTRUCTION

- Silver coated high strength copper alloy
- Fluoropolymer/polyimide tapes Insulation

CHARACTERISTICS

- Temperature Range :200°C
- Voltage Rating : 600 Volts

CONSTRUCTION

- Nickel coated high strength copper alloy
- Fluoropolymer/polyimide tapes Insulation

CHARACTERISTICS

- Temperature Range :150°C
- Voltage Rating : 600 Volts

Specifications of MIL-W-22759/89 | SAE AS22759/89 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.033	0.037
24	19/36	0.038	0.042
22	19/34	0.043	0.047
20	19/32	0.051	0.055

Specifications of MIL-W-22759/90 | SAE AS22759/90 Wire

AWG Size	Conductor Stranding	Min O.D. (in)	Max O.D. (in)
26	19/38	0.033	0.037
24	19/36	0.038	0.042
22	19/34	0.043	0.047
20	19/32	0.051	0.055