



PVC 3 & 4 Core Auto Cable BS 6862

(Flat Twins & Round Twins)



PVC 3 Core Auto Cables

Manufactured in accordance with BS 6862 Part1 1971, where applicable.
Plain copper conductors
PVC insulated and sheathed 70°C.

PVC 4 Core Auto Cables

Manufactured in accordance with BS 6862 Part1 1971, where applicable.
Plain copper conductors
PVC insulated and sheathed 70°C.

Specifications of PVC Auto Cable BS 6862 (3 Core)

Conductor Specification (mm)	Conductor Cross Section mm ² (AWG)	Current Rating (Amps)	Overall Diameter of Cables (mm)	Sheath Colours	Core Colours
3 x 9/0.30	3 x 0.65 (19)	5.75	7.0	Black	Black
3 x 14/0.30	3 x 1.0 (17)	8.75	7.5	Black	Green
3 x 21/0.30	3 x 1.5 (15)	12.75	8.0	Black	Red
3 x 28/0.30	3 x 2.0 (14)	17.5	8.5	Black	

Specifications of PVC Auto Cable BS 6862 (4 Core)

Conductor Specification (mm)	Conductor Cross Section mm ² (AWG)	Current Rating (Amps)	Overall Diameter of Cables (mm)	Sheath Colours	Core Colours
3 x 9/0.30	4 x 0.65 (19)	5.75	7.5	Black	Brown
3 x 14/0.30	4 x 1.0 (17)	8.75	8.1	Black	Green
3 x 21/0.30	4 x 1.5 (15)	12.75	9.0	Black	Red White

*Available in difference colors, lengths, wound on card board, Plastic (Shatter Proof Material) or Wooden Reels.