



Starter / Battery Cables & Speaker Wire



Starter/Battery Cable

CONSTRUCTION

- Stranded
- Bare Copper
- PVC Insulation

CHARACTERISTICS

- Temperature Range : -15°C to +70°C
- Resistant to petrol, lubricating oils and diluted acids.

APPLICATION

- Starter/Battery Cables may be used for engine and battery connectors in commercial vehicles.

Speaker Wire

CONSTRUCTION

- Stranded
- Bare Copper
- PVC Insulation

CHARACTERISTICS

- Temperature Range : -15°C to +70°C

APPLICATION

- Twin Flat figure of 8 Cables suitable for wiring speaker systems in vehicles and the home

Specifications of Starter / Battery Cable

Conductor Specification (mm)	Conductor Cross Section mm ²	Current Rating (Amps)	Maximam Overall Diameter of Cables (mm)	Resistance per Metre at 200C (Ohms)	Sheath Colours
266/0.30	20 (4)	135	9.5	0.0010	Black, Red
196/0.40	25 (3)	170	9.8	0.0008	Black, Red
315/0.40	40 (1)	300	12.2	0.0005	Black, Red
396/0.40	50 (1/0)	345	13.3	0.0004	Black, Red
475/0.40	60 (2/0)	415	14.6	0.0003	Black, Red

Specifications of Speaker Wire

Conductor Specification (mm)	Conductor Cross Section mm ²	Overall Diameter of Cables (mm)	Current Rating (Amps)	Sheath Colours
2 X 12/0.20	2 X 0.38 (21)	3.6 X 1.7	2	Black - Black/White
2 X 16/0.20	2 X 0.5 (20)	3.9 X 1.9	3	Black - Black/White
2 X 24/0.20	2 X 0.75 (18)	4.3 X 2.1	6	Black - Black/Red
2 X 32/0.20	2 X 1.0 (17)	4.6 X 2.3	10	Black - Black/Blue
2 X 21/0.30	2 X 1.5 (15)	5.9 X 2.8	15	Transparent - Trans/Green
2 X 35/0.30	2 X 2.5 (13)	6.7 X 3.0	20	Transparent - Trans/Yellow