



Thin Wall 3 & 4 Core Auto Cable



Thin Wall 3 Core Auto Cables

- Cores manufactured to ISO 6722 : 2006 (Class B) 105°C.
- Plain copper conductors PVC insulated and sheathed 70°C.

Thin Wall 4 Core Auto Cables

- Cores manufactured to ISO 6722 : 2006 (Class B) 105°C.
- Plain copper conductors PVC insulated and sheathed 70°C.

Specifications of Thin Wall Auto Cable (3 Core)

| Conductor Specification (mm) | Conductor Cross Section mm ² | Nominal Current Rating (Amps) | Maximum Overall Dimensions of Cables (mm) | Sheath Colours | Core Colours |
|------------------------------|-----------------------------------------|-------------------------------|-------------------------------------------|----------------|--------------|
| 3 x 24/0.20 | 3 x 0.75 | 14.0 | 5.6 | Black | |
| 3 x 32/0.20 | 3 x 1.0 | 16.5 | 5.6 | Black | Black |
| 3 x 21/0.30 | 3 x 1.5 | 21.0 | 6.8 | Black | Red |
| 3 x 28/0.30 | 3 x 2.0 | 25.0 | 7.3 | Black | Green |

Specifications of Thin Wall Auto Cable (4 Core)

| Conductor Specification (mm) | Conductor Cross Section mm ² | Nominal Current Rating (Amps) | Maximum Overall Dimensions of Cables (mm) | Sheath Colours | Core Colours |
|------------------------------|-----------------------------------------|-------------------------------|-------------------------------------------|----------------|--------------|
| 4 x 24/0.20 | 4 x 0.75 | 14.0 | 5.8 | Black | Brown |
| 4 x 32/0.20 | 4 x 1.0 | 16.5 | 5.8 | Black | Green |
| 4 x 21/0.30 | 4 x 1.5 | 21.0 | 7.6 | Black | Red White |