



## Thin Wall 5 & 7 Core Auto Cable



### Thin Wall 5 Core Auto Cables

- Cores manufactured to ISO 6722 : 2006 (Class B) 105°C.
- Plain copper conductors PVC insulated and sheathed 70°C.

### Thin Wall 7 Core Auto Cables

- Cores manufactured to ISO 6722 : 2006 (Class B) 105°C.
- Plain copper conductors PVC insulated and sheathed 70°C.

### Specifications of Thin Wall Auto Cable (5 Core)

Conductor Specification (mm)	Conductor Cross Section mm <sup>2</sup>	Nominal Current Rating (Amps)	Maximum Overall Dimensions of Cables (mm)	Sheath Colours	Core Colours
5 x 24/0.20	5 x 0.75	14.0	6.3	Black	Brown
5 x 32/0.20	5 x 1.0	16.5	6.3	Black	Green
4 x 32/0.20	4 x 1.0	16.5	7.6	Black	Red
1 x 28/0.30	1 x 2.0	25.0			White
					Yellow

### Specifications of Thin Wall Auto Cable (7 Core)

Conductor Specification (mm)	Conductor Cross Section mm <sup>2</sup>	Nominal Current Rating (Amps)	Maximum Overall Dimensions of Cables (mm)	Sheath Colours	Core Colours
7 x 16/0.20	7 x 0.5	11.0	7.0	Black	Black
7 x 24/0.20	7 x 0.75	14.0	6.8	Black	Red
7 x 32/0.20	7 x 1.0	16.5	7.4	Black	Green
6 x 32/0.20	6 x 1.0	16.5	7.8	Black	Yellow
1 x 28/0.30	1 x 2.0	25.0			Brown
6 x 21/0.30	6 x 1.5	21.0	10.1	Grey	White
1 x 35/0.30	1 x 2.5	29.0			Blue