



## Multi-Conductor Computer Cable - Foil & Braided Overall



### Multi-Conductor Computer Cable (Foil/Braid Shield) UL 2464, UL 2919, NEC TYPE CM and CL2, CSA CMG

#### COMPLIANCES

- NEC Article 800 Type CM (UL:75°C) (20 AWG only)
- NEC Article 800 Type CMR (UL:75°C) (22-24 AWG)
- UL Style 2464 (UL: 80°C, 300 Volts)
- CSA CMG (CSA: 60°C)
- Passes UL 70,000 BTU Vertical Tray Flame Test
- Passes CSA CMG Flame Test
- RoHS Compliant

#### CONSTRUCTION

- Conductor :
- Fully annealed stranded tinned copper per ASTM B-33
- Insulation :
- Premium grade, color-coded SR-PVC (22-24 AWG) and PVC (20 AWG)
- Shield :
- 100% Aluminum/Polyester Foil Shield
- 25% overlap, foil facing out
- Stranded Tinned Copper Drain Wire
- Jacket :
- Material : PVC
- Color : Gray
- Nom. Jacket Thickness (in) : 0.032
- Temperature Range : -20°C to + 80°C

#### APPLICATIONS

- Suitable for EIA RS-232 applications
- Computer Interconnections
- Control circuits
- Industrial equipment controls
- Data transmissions
- Suggested voltage rating : 300 volts