



Hook-Up Wire / Lead Wire

UL 1275 & UI 1056



UL 1275 / UL 1056 Hook Up Wire

Polyvinylchloride (PVC)
Heavy Wall Lead Wire, Hook Up Wire
and Refrigeration
(105°C) (VW-1 & Moisture Resistant)
(600 Volts) (UL & CSA)
* RoHS Available

APPLICATION UL 1275 / UL 1056

- UL 1275 Lead Wire: UL 1275 may be used for internal wiring of refrigerating equipment.
- UL 1275 is resistant to oil at temperatures not exceeding 60°C or 80°C if applicable.
- UL 1056 Lead Wire: UL 1056 may be used for internal wiring of indoor or outdoor refrigerating equipment - UL 1056 is oil resistance 60°C or 80°C (if applicable).

Specifications of UL 1275 & UI 1056 Wire

AWG Size	Conductor Stranding	Nom. Insul. Thick. (in)	Nom. O.D. (in)	Approx LBS/MFT
18	16/30	0.060	0.174	18
18	16/30	0.060	0.174	18
16	26/30	0.060	0.186	22
16	26/30	0.060	0.186	22
14	41/30	0.060	0.196	28
12	65/30	0.060	0.212	37
10	10/30	0.060	0.240	53